


HILTI

Hilti HCC-B
shear connector





Drill the holes using the Hilti TE 70-AVR rotary hammer and Hilti TE-C3X 16/47 drill bits.



Clean the holes by brushing and blowing out with compressed air using the appropriate Hilti accessories.



Set the shear connectors using Hilti setting tools featuring TE-C or TE-Y connection ends.



Inject Hilti RE 500 adhesive mortar through the funnel-shaped opening in the shear connector.

Connections with cost-efficiency advantages.

Concrete overlays with the Hilti HCC-B.

Using the Hilti HCC-B shear connector and Hilti HIT-RE 500 injectable adhesive, a new layer of concrete can be bonded to old concrete permanently, reliably and with high resistance to shear forces at only a fraction of the cost of reconstruction. But that's not all. Hilti supplies a complete cost-efficient system for structural reinforcement and repair using the concrete overlay method.

Applications

- Concrete overlays
- Bridge renovation and repair
- Strengthening bridges for higher loads
- Strengthening concrete decks for higher loads, i.e. conversion for other uses
- Reinforcing foundations, pillars, supports and walls


Advantages

- Easy to use – the connectors require no beforehand preparation
- Quick – leveling and height adjustment is possible during installation
- The connectors can be loaded immediately after setting thanks to their frictional hold
- Easy visual check to ensure injection of the optimum mortar quantity, internal injection system for reliable filling
- Reliable design – the structure displays monolithic behaviour

Highlights

This complete system of matched components including a PC application for easy design, high-performance rotary hammers, Hilti HIT injectable adhesive mortars, mortar dispensers and the HCC-B shear connector provides the key to efficient and reliable concrete overlays.

Setting instructions



Performance data

Base material	Cracked and uncracked concrete \geq C20/25 (B25)
Drilling method	Hammer drilling
Connector material	Malleable cast iron
Structural design	EOTA Technical Report TR 029, technical data sheet: Concrete overlays for strengthening and repair in bridge, tunnel and building construction (item no. 241345)
Setting instructions	See HCC-B shear connector operating instructions

High system rigidity

The greater the connector's rigidity, the greater its contribution to the transmission of shear through tensile forces.




Maximum planning and design reliability

A complete design concept incorporating the Hilti Exbar Overlay PC application provides all the required design information quickly and reliably.

Radially symmetrical headed studs

The direction of shear forces is irrelevant as the connectors act as highly-robust rebar holders that keep the reinforcement in place, where it should be, even after the concrete has been poured.



Shear connector

Ordering designation

Hilti HCC-B shear connector, in packs of 100

Item no.

① 378921

Injectable adhesive mortar

Hilti HIT-RE 500 injectable adhesive mortar, 330 ml

② 305074

Hilti HIT-RE 500 injectable adhesive mortar, 500 ml

369109

Hilti HIT-RE 500 injectable adhesive mortar, 1400 ml

373958

Dispensers

Hilti MD 2500 manual dispenser for 330 and 500 ml foil packs

③ 338853

Hilti MD 3500 cordless electric dispenser for 330 and 500 ml foil packs

273291

Hilti P 8000 D pneumatic dispenser for 1400 ml foil packs

373959

Accessories

HSD-M M12 1/2" x 50 (TE-C) setting tool

④ 243752

HCC-M (TE-Y) setting tool

379723

HIT-VL 16/0.7 extension tube

024632

HIT-RB 12 round brush

⑤ 336550

TE-C holder for round brushes

263437

TE-Y holder for round brushes

⑥ 263439

HIT-RBS 10/0.7 brush extension 70 cm

336645

HIT-RBS 10/0.35 brush extension 35 cm

⑦ 371722



Productivity plus



Rotating lasers for easy, accurate leveling and alignment



Powerful rotary hammers for tough drilling jobs



Drill bits perfectly matched to Hilti tools for maximum performance and productivity



Innovative tool management reduces your costs by up to 50 %

Hilti. Outperform. Outlast.

Hilti Corporation | 9494 Schaan | Liechtenstein | P +423-234 2111 | F +423-234 2965 | www.hilti.com