

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 04/10/2016 Revision date: 04/10/2016 Supersedes: 06/08/2013 Version: 23.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form Mixture
Name GC 11

Product code BU Direct Fastening

Vaporizer Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec For professional use only

Use of the substance/mixture Gas can for use exclusively with the Hilti GX 100 tool

Propellant for direct fastening tools

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier Department issuing data specification sheet

Hilti (Gt. Britain) Ltd. Hilti Entwicklungsgesellschaft mbH

1 Trafford Wharf Road Hiltistrasse 6

M17 1BY Manchester - Great Britain 86916 Kaufering - Deutschland

T +44 161 886 1000 T +49 8191 906310 - F +49 8191 90176310

0800 886 100 Toll-free - F +44 161 872 1240 <u>df-hse@hilti.com</u>

gbsales@hilti.com

1.4. Emergency telephone number

Emergency number Schweizerisches Toxikologisches Informationszentrum – 24h Service

+41 44 251 51 51 (international)

+44 161 886 1000 0800 886 100 Toll-free

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229

Full text of hazard classes and H-statements : see section 16

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP) Danger

Hazard statements (CLP) H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

Precautionary statements (CLP) P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

04/10/2016 GB - en 1/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dimethyl ether	(CAS No) 115-10-6 (EC no) 204-065-8 (EC index no) 603-019-00-8	20 - <30	Flam. Gas 1, H220 Compressed gas, H280
propene	(CAS No) 115-07-1 (EC no) 204-062-1 (EC index no) 601-011-00-9	20 - <30	Flam. Gas 1, H220 Compressed gas, H280
Isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0	10 - <20	Flam. Gas 1, H220 Compressed gas, H280
ethanol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	10 - <20	Flam. Liq. 2, H225
Propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	5 - <15	Flam. Gas 1, H220 Compressed gas, H280
Butane	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	5 - 10	Flam. Gas 1, H220 Compressed gas, H280

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general Remove/Take off immediately all contaminated clothing.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact Gently wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention.

First-aid measures after eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation Shortness of breath.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

04/10/2016 GB - en 2/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray. Carbon dioxide. Dry powder. Foam. Sand.

Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard Extremely flammable aerosol.

Explosion hazard Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

Hazardous decomposition products in case of

Formation of toxic gases is possible during heating or in case of fire. Thermal decomposition

generates: Carbon dioxide. Carbon monoxide.

5.3. Advice for firefighters

fire

Precautionary measures fire Fight fire remotely due to the risk of explosion.

Firefighting instructions DO NOT fight fire when fire reaches explosives. Evacuate area.

Do not enter fire area without proper protective equipment, including respiratory protection. Protection during firefighting

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Evacuate area. No flames, no sparks. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

Emergency procedures Ventilate spillage area. Avoid breathing vapours. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Do not attempt to take action without suitable protective equipment. Breathing apparatus.

Emergency procedures Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Do not flush with water. Methods for cleaning up

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or

burn, even after use

Precautions for safe handling Do not eat, drink or smoke when using this product. Do not breathe vapours. Avoid contact with

skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Proper grounding procedures to avoid static electricity should be followed.

Storage conditions Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Keep in fireproof place.

Incompatible materials Heat sources. Direct sunlight.

04/10/2016 GB - en 3/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Storage temperature 5 - 25 °C

Heat and ignition sources

Keep away from heat and direct sunlight.

Prohibitions on mixed storage

Do not store with DX powder cartridges.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dimethyl ether (115-10-6)			
EU	Local name	Dimethylether	
EU	IOELV TWA (mg/m³)	1920 mg/m³	
EU	IOELV TWA (ppm)	1000 ppm	
United Kingdom	Local name	Dimethyl ether	
United Kingdom	WEL TWA (mg/m³)	766 mg/m ³	
United Kingdom	WEL TWA (ppm)	400 ppm	
United Kingdom	WEL STEL (mg/m³)	958 mg/m³	
United Kingdom	WEL STEL (ppm)	500 ppm	
ethanol (64-17-5)			
United Kingdom	Local name	Ethanol	
United Kingdom	WEL TWA (mg/m³)	1920 mg/m³	
United Kingdom	WEL TWA (ppm)	1000 ppm	
Butane (106-97-8)			
United Kingdom	Local name	Butane	
United Kingdom	WEL TWA (mg/m³)	1450 mg/m³	
United Kingdom	WEL TWA (ppm)	600 ppm	
United Kingdom	WEL STEL (mg/m³)	1810 mg/m³	
United Kingdom	WEL STEL (ppm)	750 ppm	
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	

8.2. Exposure controls

Hand protection In case of repeated or prolonged contact wear gloves

Туре	Material	Permeation	Thickness (mm)	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	EN 374

Eye protection Chemical goggles or safety glasses. EN 166. EN 170

Туре	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection

When using setting tools, sufficient ear protection must be worn







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Gas
Colour Colourless.
Odour characteristic.

04/10/2016 GB - en 4/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold No data available No data available No data available Relative evaporation rate (butylacetate=1) No data available Melting point No data available Freezing point Boiling point No data available No data available Flash point < 300 °C Auto-ignition temperature

Decomposition temperature No data available Flammability (solid, gas) No data available 8300 hPa @ 20°C Vapour pressure Relative vapour density at 20 °C No data available Relative density No data available

Density 1.02 g/cm3 (DIN 51757), @20°C

Solubility Insoluble in water. Log Pow No data available No data available Viscosity, kinematic Viscosity, dynamic No data available

Product is not explosive. In use may form flammable/explosive vapour-air mixture. Explosive properties

No data available Oxidising properties 1.7 vol % Explosive limits 18.6 vol %

9.2. Other information

VOC content 1018.6 mg/l EU-VOC

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Not classified Acute toxicity

04/10/2016 GB - en 5/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Dimethyl ether (115-10-6)	ı		
LC50 inhalation rat (mg/l)	309 mg/l/4h (Rat; Literature study)		
LC50 inhalation rat (ppm)	164000 ppm/4h (Rat; Literature study)		
propene (115-07-1)			
LC50 inhalation rat (mg/l)	658 mg/l/4h (Rat; Literature)		
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1 000 mg/n-m (reat, Enterature)		
Isobutane (75-28-5) LC50 inhalation rat (mg/l)	> 50 mg/l/4h (Rat; Literature study)		
LC50 inhalation rat (ppm)	11000 ppm		
	11000 ppm		
ethanol (64-17-5) LD50 oral rat	10740 mg/kg bodyweight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)		
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)		
	> 10000 mg/kg (Nabbit, Eliciature Study)		
Propane (74-98-6) LC50 inhalation rat (mg/l)	513 mg/l/4h (Rat; Literature)		
LC50 inhalation rat (mg/l)	280000 ppm/4h (Rat; Literature)		
W I	200000 ppm/4m (Nat, Eiterature)		
Butane (106-97-8) LC50 inhalation rat (mg/l)	658 mg/l/4h (Rat; Literature)		
LC50 inhalation rat (ppm)	276000 ppm/4h (Rat; Literature)		
Skin corrosion/irritation	Not classified		
Serious eye damage/irritation	Not classified		
Respiratory or skin sensitisation	Not classified		
Germ cell mutagenicity	Not classified		
Reproductive toxicity	Not classified		
Specific target organ toxicity (single exposure)	Not classified		
Specific target organ toxicity (repeated exposure)	Not classified		
Aspiration hazard	Not classified		
GC 11			
Vaporizer	Aerosol		

SECTION 12: Ecological information

12.1. Toxicity

Dimethyl ether (115-10-6)			
LC50 fish 1	3082 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 1	756.2 mg/l (48 h; Daphnia magna)		
LC50 fish 2	> 1000 mg/l (96 h; Pisces)		
EC50 Daphnia 2	> 4400 mg/l (48 h; Daphnia magna)		
Threshold limit algae 1	154.9 mg/l (96 h; Algae)		
propene (115-07-1)			
Threshold limit algae 1	3 - 15,Algae; QSAR		
Threshold limit algae 2	10 - 100,Algae; Estimated value		
Isobutane (75-28-5)			
Threshold limit algae 1	1.07 mg/l (Algae)		
Threshold limit algae 2	7.15 mg/l (72 h; Algae)		
ethanol (64-17-5)			
LC50 fish 1	14200 mg/l (96 h; Pimephales promelas; Nominal concentration)		
EC50 Daphnia 1	9300 mg/l (48 h; Daphnia magna)		
LC50 fish 2	13000 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 2	10800 mg/l (24 h; Daphnia magna)		
Threshold limit other aquatic organisms 1	65 mg/l (72 h; Protozoa)		
Threshold limit algae 1	1450 mg/l (192 h; Microcystis aeruginosa; Growth rate)		
Threshold limit algae 2	5000 mg/l (168 h; Scenedesmus quadricauda; Growth rate)		
Propane (74-98-6)			
TLM fish 1	17.8 - 19.7,96 h; Pimephales promelas		
Threshold limit algae 1	1.45 - 4.53,72 h; Algae		
Threshold limit algae 2	8 mg/l (72 h; Algae)		
Butane (106-97-8)			
TLM fish 1	1000 mg/l (96 h; Pisces)		

04/10/2016 GB - en 6/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Threshold limit other aquatic organisms 1	0.6 - 0.9,504 h; Daphnia magna
Threshold limit algae 1	0.88 - 1.76,Algae

12.2. Persistence and degradability

Dimethyl ether (115-10-6)		
Persistence and degradability	Not readily biodegradable in water. Non degradable in the soil. Not applicable (gas).	
propene (115-07-1)		
Persistence and degradability	Not readily biodegradable in water. Inherently biodegradable. Biodegradable in the soil. Ozonation in the air. Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0 g O₂/g substance	
ThOD	3.43 g O₂/g substance	
BOD (% of ThOD)	(5 day(s)) 0	
Isobutane (75-28-5)		
Persistence and degradability	Inherently biodegradable. Biodegradable in the soil. Not applicable (gas).	
ethanol (64-17-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available.	
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O₂/g substance	
Chemical oxygen demand (COD)	1.70 g O₂/g substance	
ThOD	2.10 g O₂/g substance	
Propane (74-98-6)		
Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.	
Butane (106-97-8)		
Persistence and degradability	Readily biodegradable in water.	

12.3. Bioaccumulative potential

Dimethyl ether (115-10-6)	
Log Pow	0.10 (Experimental value; 0.07; QSAR; KOWWIN; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
propene (115-07-1)	
Log Pow	1.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Isobutane (75-28-5)	
BCF fish 1	20 - 52 (Pisces; QSAR)
BCF other aquatic organisms 1	20 - 52 (Daphnia magna; QSAR)
Log Pow	2.8 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
ethanol (64-17-5)	
Log Pow	-0.35 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 24 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Propane (74-98-6)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Butane (106-97-8)	
Log Pow	2.89 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Dimethyl ether (115-10-6)	
Surface tension	0.020 N/m (-40 °C)
propene (115-07-1)	
Surface tension	0.02 N/m (-50 °C)
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
Isobutane (75-28-5)	
Surface tension	0.014 N/m (-10 °C)
ethanol (64-17-5)	
Surface tension	0.0245 N/m (20 °C)

04/10/2016 GB - en 7/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propane (74-98-6)	
Surface tension	0.016 N/m (-47 °C)
Butane (106-97-8)	
Surface tension	< 0.1 N/m (0 °C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) Disposal must be done according to official regulations.

Waste treatment methods Dispose of contents/container in accordance with licensed collector's sorting instructions.

Waste disposal recommendations Container under pressure. Do not drill or burn even after use.

Additional information Flammable vapours may accumulate in the container.

European List of Waste (LoW) code 14 06 03* - other solvents and solvent mixtures

16 05 04* - gases in pressure containers (including halons) containing dangerous substances

15 01 04 - metallic packaging

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

Other information No supplementary information available

ADR	IMDG	IATA	RID		
14.1. UN number					
1950	1950	1950	1950		
14.2. UN proper shipping nan	ne				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS		
Transport document descript	tion	•			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1				
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1		
2	2	2	" S		
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards	14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No		
No supplementary information available					

04/10/2016 GB - en 8/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

- Overland transport

Classification code (ADR) 5F

Special provisions (ADR) 190, 327, 344, 625

Limited quantities (ADR)

Packing instructions (ADR) P207, LP02
Mixed packing provisions (ADR) MP9
Tunnel restriction code (ADR) D

- Transport by sea

Special provisions (IMDG) 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) SP277
Packing instructions (IMDG) P207, LP02
EmS-No. (Fire) F-D

EmS-No. (Spillage) S-U Stowage category (IMDG) None

Stowage and segregation (IMDG) Protected from sources of heat For AEROSOLS with a maximum capacity of 1 litre: Category

A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the

appropriate sub-division of class 2.

MFAG-No 126

- Air transport

PCA packing instructions (IATA) 203
PCA max net quantity (IATA) 75kg
Special provisions (IATA) A145, A167

- Rail transport

Special provisions (RID) 190, 327, 344, 625

Limited quantities (RID) 1L

Packing instructions (RID) P207, LP02

Carriage prohibited (RID) No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content 1018.6 mg/l EU-VOC

15.1.2. National regulations

15.2. Chemical safety assessment

No additional information available

04/10/2016 GB - en 9/10



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:

Aerosol 1	Aerosol, Category 1	
Compressed gas	Gases under pressure : Compressed gas	
Flam. Gas 1	Flammable gases, Category 1	
Flam. Liq. 2	Flammable liquids, Category 2	
H220	Extremely flammable gas	
H222	Extremely flammable aerosol	
H225	Highly flammable liquid and vapour	
H229	Pressurised container: May burst if heated	
H280	Contains gas under pressure; may explode if heated	

SDS_EU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

04/10/2016 GB - en 10/10